

PATENT

CLAIMS

1. (Currently Amended) An encoding method for reducing decoding complexity, the method comprising:

encoding systematic bits in each of a plurality of buffers with a first code;

multiplexing content of the plurality of buffers; and

encoding said multiplexed content with a second code to provide a set of frames, wherein the encoding comprises identifying a block of bits to be encoded and then coding the block of bits with the second code.

2. (Previously Presented) The method as claimed in claim 1 wherein said encoding systematic bits in each of the plurality of buffers with the first code comprises:

encoding systematic bits in each of the plurality of buffers with a block code.

3. (Previously Presented) The method as claimed in claim 2 wherein said encoding systematic bits in each of the plurality of buffers with a block code comprises:

encoding systematic bits in each of the plurality of buffers with a Reed-Solomon code.

4. (Original) The method as claimed in claim 1 wherein said multiplexing content of the plurality of buffers comprises:

providing a block of bits successively from each of the plurality of buffers.

5. (Previously Presented) The method claimed in claim 4 wherein said providing the block of bits successively from each of the plurality of buffers comprises:

providing the block of bits comprising a row of each of the plurality of buffers.

6. (Cancelled)

PATENT

7. (Currently Amended) The method claimed in claim 1 ~~[[6]]~~ wherein said identifying the block of bits to be encoded comprises:

identifying the block of bits received from at least one of the plurality of buffers.

8. (Currently Amended) A method reducing decoding complexity, comprising:

decoding received frames by a ~~second~~ first decoder;

de-multiplexing correctly decoded frame to a plurality of buffers, wherein the de-multiplexing comprises identifying a block of bits comprising a frame decoded by the first decoder and belonging to at least one of the plurality of buffers, and further providing the block of bits to at least one of the plurality of buffers; and

processing content of each of the plurality of buffers.

9. (Cancelled)

10. (Cancelled)

11. (Original) The method as claimed in claim 8 wherein said processing content of each of the plurality of buffers comprises:

providing systematic portion of each of the plurality of buffers to higher layers.

12. (Currently Amended) The method as claimed in claim 8 further comprising:

providing indication of an erasure to ~~the-second~~ a second decoder communicatively coupled to at least one of the plurality of buffers that would receive the correctly decoded frame if the frame failed to decode correctly.

13. (Previously Presented) The method as claimed in claim 12 wherein said processing content of each of the plurality of buffers comprises:

PATENT

decoding the systematic portion of the buffer by the second decoder when the systematic portion is recoverable; and
providing the systematic portion of each of the plurality of buffer to higher layers.

14. (Currently Amended) A method for reducing decoding complexity, comprising:
encoding systematic bits in each of a plurality of transmit buffers with a first code;
multiplexing content of the plurality of transmit buffers;
encoding said multiplexed content with a second code to provide a set of frames, wherein said encoding comprises identifying a block of bits to be encoded then coding the block of bits with the second code;

transmitting the set of frames;
decoding received frames by a ~~second~~ first decoder;
de-multiplexing correctly decoded frame to a plurality of receive buffers; and
processing content of each received buffer.

15. (Previously Presented) The method as claimed in claim 14 wherein said encoding systematic bits in each of the plurality of transmit buffers with a first code comprises:
encoding systematic bits in each of the plurality of transmit buffers with a block code.

16. (Previously Presented) The method as claimed in claim 15 wherein said encoding systematic bits in each of the plurality of buffers with the block code comprises:
encoding systematic bits in each of a plurality of buffers with a Reed-Solomon code.

17. (Previously Presented) The method as claimed in claim 14 wherein said multiplexing content of the plurality of the transmit buffers comprises:
providing a block of bits successively from each buffer.

18. (Previously Presented) The method claimed in claim 17 wherein said providing the block of bits successively from each buffer comprises:

PATENT

providing the block of bits comprising a row of at least one of the plurality of transmitting buffers.

19. (Cancelled)

20. (Currently Amended) The method claimed in claim 14 [[19]] wherein said identifying the block of bits to be encoded comprises:

identifying the block of bits as the block of bits received from at least one of the plurality of transmit buffers.

21. (Previously Presented) The method as claimed in claim 14 wherein said demultiplexing correctly decoded frame to a receive buffers comprises:

identifying a block of bits belonging to at least one of the plurality of receive buffers; and providing the block of bits to at least one of the plurality of receive buffers.

22. (Currently Amended) The method as claimed in claim 21 wherein said identifying the block of bits belonging to at least one of the plurality of receive buffers. comprises:

identifying the block of bits as a block of bits comprising a frame decoded by the second first decoder.

23. (Original) The method as claimed in claim 14 wherein said processing content of each receive buffer comprises:

providing systematic portion of each buffer to higher layers.

24. (Currently Amended) The method as claimed in claim 14 further comprising:

providing indication of an erasure to a first second decoder communicatively coupled to the receive buffer that would receive the correctly decoded frame if the frame failed to decode correctly.

PATENT

25. (Previously Presented) The method as claimed in claim 24 wherein said processing content of each buffer comprises:

decoding the systematic portion of at least one of the plurality of receive buffers by the first decoder when the systematic portion is recoverable; and
providing systematic portion of each buffer to higher layers.

26. (Currently Amended) An apparatus for reducing decoding complexity, comprising:

a plurality of buffers;

a plurality of encoders, each of said plurality of encoders being communicatively coupled to one of said plurality of buffers;

a multiplexer communicatively coupled to said plurality of buffers; and

an inner encoder communicatively coupled to said multiplexer, wherein the inner encoder is configured to identify a block of bits to be encoded and encode the block of bits with an inner code.

27. (Original) The apparatus as claimed in claim 26 wherein each of said plurality of buffers is configured to:

store systematic bits and parity bits.

28. (Previously Presented) The apparatus as claimed in claim 26 wherein each of said plurality of encoders is configured to:

encode systematic bits to provide parity bits.

29. (Original) The apparatus as claimed in claim 28 wherein each of said plurality of encoders is configured to:

encode the systematic bits with a block code.

PATENT

30. (Previously Presented) The apparatus as claimed in claim 26 wherein each of said plurality of encoders is configured to:

encode the systematic bits with a Reed-Solomon code.

31. (Original) The apparatus claimed in claim 26 wherein said multiplexer is configured to:

provide a block of bits successively from each of said plurality of buffers to said inner encoder.

32. (Original) The apparatus as claimed in claim 31 wherein said block of bits comprises a row of said buffer.

33. (Cancelled)

34. (Currently Amended) The apparatus as claimed in claim 26 ~~[[33]]~~ wherein said block of bits to be encoded comprises:

a block of bits received from said multiplexer.

35. (Cancelled)

36. (Previously Presented) An apparatus for reducing decoding complexity, comprising:

a first decoder, wherein said first decoder is configured to:

decode a received frame;

provide a correctly decoded frame; and

provide indication of an erasure if the received frame failed to decode correctly.

a de-multiplexer communicatively coupled to said first decoder;

a plurality of buffers communicatively coupled to said de-multiplexer; and

a plurality of decoders, each of said plurality of decoders being communicatively coupled to one of said plurality of buffers.

PATENT

37. (Currently Amended) The apparatus as claimed in claim 36~~35~~ wherein said de-multiplexer is configured to:

identify a block of bits belonging to at least one of the plurality of buffers; and
provide the block of bits to the buffer.

38. (Previously Presented) The apparatus as claimed in claim 37 wherein said block of bits belonging to at least one of the plurality of buffers comprises:
the block of bits comprising a frame decoded by said first decoder.

39. (Currently Amended) The apparatus as claimed in claim 36~~35~~ wherein each of said plurality of decoders is configured to:
decode the systematic portion of at least one of the plurality of buffers by an outer decoder when the systematic portion is recoverable.

40. (Currently Amended) The apparatus as claimed in claim 36~~35~~ wherein each of said plurality of buffers is configured to:
provide systematic portion to higher layers.

41. (Currently Amended) An apparatus for reducing decoding complexity, comprising:

a plurality of transmit buffers;
a plurality of encoders, each of said plurality of encoders being communicatively coupled to one of said plurality of transmit buffers;
a multiplexer communicatively coupled to said plurality of transmit buffers;
an inner encoder communicatively coupled to said multiplexer, wherein the inner encoder is configured to identify a block of bits to be encoded and to encode the block of bits with an inner code;

a first decoder;

a de-multiplexer communicatively coupled to said first decoder;

a plurality of receive buffers communicatively coupled to said de-multiplexer; and

PATENT

a plurality of decoders, each of said plurality of decoders being communicatively coupled to one of said plurality of receive buffers.

42. (Original) The apparatus as claimed in claim 41 wherein each of said plurality of transmit buffers is configured to:

store systematic bits and parity bits.

43. (Previously Presented) The apparatus as claimed in claim 41 wherein each of said plurality of encoders is configured to:

encode systematic bits to provide parity bits.

44. (Original) The apparatus as claimed in claim 43 wherein each of said plurality of encoders is configured to:

encode the systematic bits with a block code.

45. (Previously Presented) The apparatus as claimed in claim 41 wherein each of said plurality of encoders is configured to:

encode the systematic bits with a Reed-Solomon code.

46. (Original) The apparatus claimed in claim 41 wherein said multiplexer is configured to:

provide a block of bits successively from each of said plurality of transmit buffers to said inner encoder.

47. (Previously Presented) The apparatus as claimed in claim 46 wherein said block of bits comprises a row of at least one of the plurality of transmit buffers.

48. (Cancelled)

PATENT

49. (Currently Amended) The apparatus as claimed in claim 41 ~~[[48]]~~ wherein the block of bits to be encoded comprises:

the block of bits received from said multiplexer.

50. (Previously Presented) The apparatus as claimed in claim 41 wherein said first decoder is configured to:

decode a received frame;

provide a correctly decoded frame; and

provide indication of an erasure if the received frame failed to decode correctly.

51. (Previously Presented) The apparatus as claimed in claim 41 wherein said de-multiplexer is configured to:

identify a block of bits belonging to at least one of the plurality of receive buffers; and

provide the block of bits to the buffer.

52. (Previously Presented) The apparatus as claimed in claim 51 wherein said block of bits belonging to the buffer comprises:

the block of bits comprising a frame decoded by said first decoder.

53. (Previously Presented) The apparatus as claimed in claim 41 wherein each of said plurality of decoders is configured to:

decode the systematic portion of at least one of the plurality of receive buffers by an outer decoder when the systematic portion is recoverable.

54. (Previously Presented) The apparatus as claimed in claim 41 wherein each of said plurality of buffers is configured to:

provide systematic portion of at least one of the plurality of receive buffers to higher layers.